

- ✓ *Four Auto-sensing 10/100 Base-T Ethernet ports*
- ✓ *Compliant to RFC 2516 PPP and LCP*
- ✓ *128 Independently addressable links*
- ✓ *Four high speed (entire E1) and 124 configurable links*
- ✓ *Creates PPP, HDLC or Frame relay backbone for local Command and Control functions*
- ✓ *ARP and RIP with RIPv2 support*
- ✓ *Up to two cards per IMACS shelf*

The IP Router Bridging card allows IP services to be transported over the existing TDM network currently being used for IMACS TDM services.

The IMACS enhanced IP routing (IPR*4) card (PRM-883270) provides four 10/100Mbps Ethernet interface ports on the IMACS which allows customers to use the existing TDM network to transport IP services. The enhanced IPR*4 card enables customers to integrate and deploy IP services into remote locations currently only fed by E1s or T1s without a major investment or network upgrade. Many of these locations currently have IMACS products for muxing TDM services. Now the IMACS can also be used to bridge and transport remote IP based devices. Any currently deployed IMACS (IMACS-600/800/900) can be upgraded to accommodate the enhanced IPR*4 card allowing customers to easily add IP services to any IMACS systems already in use.

The enhanced IPR*4 card has four 10/100Mbps Ethernet ports that can be used independently as routing ports to allow for ease of provisioning, multiple configurations and different implementations as needed.

The enhanced card will support all of the same feature sets as the original IPR card, plus many new features and protocols that will allow users to seamlessly upgrade and grow their IMACS and IP networks without having to replace current platforms or upgrade to incorporate future technologies.



Technical Specifications

Dimensions

- 8.0in H x 0.94in W x 7.5in D
- 20.32cm H x 2.39cm W x 19.05cm D
- IMACS 600 (HWD):
 - 9.12 in. x 17 in. x 9.12 in.
 - 23.16 cm x 43.2 cm x 23.16 cm
- IMACS 800 (HWD):
 - 9.12 in. x 17 in. x 15.3 in.
 - 23.16 cm x 43.2 cm x 38.86 cm
- IMACS 900 (HWD):
 - 15.4 in. x 17 in. x 9.12 in.
 - 39.12 cm x 43.2 cm x 23.16 cm

Weight

- .75 lbs (.34kg)

Power

- IMACS Shelf:
- 120 / 240 VAC
- 48 VDC
- 24 VDC (IMACS 600, 800, 900 only)
- Power consumption: 125 W (max)
- Output Power: 55 W continuous
- AC-to-DC power converter (-48 VDC)
- Dual feed & redundancy
- Ring generation

Interfaces

- 4 10/100 Ethernet ports
- 124 single-DSO uplink ports
- Four high-speed uplink ports - an entire E1 on each port
- Three interface types to choose from: PPP HDLC Frame Relay

Standards Support

- RFC 2516 PPP and LCP
- RFC 1661 SNMP over OSI
- IPv4

Management

- MANAGEMENT INTERFACES
 - Connectivity: modem, SLIP, PPP, FDL time slot 24 (T1) or SAA time slot 31 (E1), ISDN D-channel, frame relay PVC
 - SNMP
- ONLINE ELEMENT MANAGEMENT SYSTEM
 - Manages networks of IMACS
 - Centralized management
 - Operates on SUN Solaris/HP OpenView
 - Point & click graphical user interface
 - Management of configurations, alarms, connectivity, diagnostics
 - Multi-user environment
 - SNMP-based
 - Supports TELNET for emulation of craft interface
 - IP addressing for node addresses
 - RS-232, VT-100 craft interface

Operating Requirements

- Operating Temperature: 32°F to 149°F (0°C to 65°C)
- Storage temperature: 32°F to 158°F (0°C to 70°C)
- Humidity: Up to 85%, non-condensing
- Altitude: -200ft to 16,500ft (-60m to 5,000m)

Zhone Technologies, Inc.

7195 Oakport Street
Oakland, CA 94621
1 510.777.7000
www.zhone.com

For more information about Zhone and its products, please visit the Zhone Web site at www.zhone.com or e-mail info@zhone.com

Zhone, the Zhone logo, and all Zhone product names are trademarks of Zhone Technologies, Inc. Other brand and product names are trademarks of their respective holders. Specifications, products, and/or product names are all subject to change without notice. Copyright 2011 Zhone Technologies, Inc. All rights reserved.

